



Tumble dryer

T5300LE

Features and benefits

- With Compass Pro program control
 - Large and clear display for easy program selection
 - Easy access with user-friendly interface
 - Language selection
 - Service program for adjustment of parameters
 - USB connection
- Heat pump Tumble Dryer
- Low energy consumption
- Exhaust duct not needed
- Reversing drum
- Residual moisture control – RMC
- Large door opening for easy loading and unloading
- Anti-wrinkle function
- Built-in service program

Main options

- Stainless steel drum



Main specifications		T5300LE	
Rated capacity, filling factor 1:50/1:30	kg	6/10	
Drum volume	litre	300	
Drum diameter	mm	760	
Heat pump effect	kW	3	
Consumption data*			
Status at start		Warm	Cold
Drying time*	min	31/43	37/51
Energy consumption**	kWh	1.33/1.93	1.40/2.04
Energy/Water evaporation	kWh/l	0.44/0.39	0.47/0.41
Energy/Load of linen	kWh/kg	0.22/0.19	0.23/0.20
* At rated capacity mixed cotton load at 50% initial moisture dried to 0%.			
** With ambient temperature of 22 degrees.			

Certified in accordance with ISO 9001 and ISO 14001 and approved IP X4.



Electrical connections		T5300LE	
Heating Voltage			
400-415V 3NAC 50 Hz	kW(A)	4 (10)	
230-240V 3AC 50 Hz	kW(A)	4 (16)	
440V 3AC 60 Hz	kW(A)	3.7 (20)	
Condense connection			
Drain diameter	∅	25	
Sound levels			
Airborne sound level	dB(A)	<70	
Heat emission			
% of installed power, max		15	
Shipping data			
	Cabinet, net, kg	120	
	Heat pump unit, net, kg	150	
	Heat pump unit with transformer, net, kg	180	
	Total net, kg	270	
Dimensions in mm			
A	Width	790	
B	Depth	1285	
C	Height	1665	
D		935	
E		740	
F		2025	
G		100	
H		270	
I		895	
J	Service access	500	
K	Service access	300	
1	Control panel	3	Electrical connection
2	Door opening ∅ 580 mm	4	Condense outlet

